

Typical Performance

FEATURES

- Wide Input voltage range (2:1、4:1)
- Typical Efficiency:91%
- Switching frequency: 300KHz $\pm$ 30 KHz
- Overcurrent,under voltage protect,short circuit protection,Self-furbish
- Input-output isolate 1500VDC
- PCB Board in-line type installs



3-Years Product Warranty

Technology parameter Test condition:General Nominal Line,Tc=25℃, Rated resistant load unless other wispecified

Input Feature	Min	Nom	Max	Notes
Input voltage(Vdc)	9	12	18	W 2:1
	18	24	36	W 2:1
	9	18	36	W 4:1
Turn on voltage	3.5Vdc		+Vin	Converter guaranteed on when REM pin is left open
Turn off voltage	0		0.3Vdc	

Under voltage protect

Output Feature

Voltage accuracy		Vo1	$\pm 1.0\%$
Line regulation		Vo1	$\pm 0.2\%$
Load regulation	20% ~ 100%	Vo1	$\pm 0.5\%$
Ripple and noise	20MHz BM Vo $\leq$ 5.0V, $\leq 50\text{mVp-p}$; Vo $\geq 48\text{V}$, $\leq 180\text{mVp-p}$; Other, $\leq 100\text{mVp-p}$;		
Dynamic response	25%	$\Delta \text{Vo1}/\Delta t$	$\pm 4.0/500\text{us}\%$
Voltage adjust	Standard output voltage	TRIM	$\pm 10\%$ (adjustable)
Start delay time	typical		$\leq 200\text{mS}$

General Feature

Efficiency	Normal input , full load	Vo≤5.0V,80% typical	Vo>5.0V, 87% typical
Switching frequency		300KHz typical	Max 330KHz
Operating temperature	Free air	Industrial level	-25℃ ~ +55℃
Storage temperature			-40℃ ~ +105℃
Max case temperature			+95℃
Relative humidity			10%~90%
case material			Metal case
Isolation Voltage	500Vdc ≤0.5mA/1min,500Vdc ≤0.5mA/1min		
MTBF	2X10 ⁵ Hrs		


Product Nomination Method

example	L D 25 - 48 S 05 I ① ② ③ ④ ⑤ ⑥ ⑦						
①	Wide input voltage: 2: 1				⑥	output voltage	
②	Power adaptation mode: D (DC-DC)				⑦	I: Dual Route output Isolate	
③	Output power(W)					W: Super Wide input voltage	
④	Normal input voltage						
⑤	S=Single route output, D=Dual route output, T=Triple route output, Q=Quadruple output						

Product Program

PART #	Input voltage range	Output voltage / current					
		VO1		VO2		VO3	
		V	mA	V	mA	V	mA
LD15-12S05C	12V(9~18V)	5V	3000mA				
LD15-12S12C		12V	1250mA				
LD15-18S05C	18V(9~36V)	5V	3000mA				
LD15-18S12C		12V	1250mA				
LD15-24S05C	24V(18~36V)	5V	3000mA				
LD15-24S12C		12V	1250mA				


Mechanical Dimension



BOTTOM VIEW

UNIT:mm(inch)

Temperature Curve



Mechanical Data

WATT	L x W x H	Packing No.
------	-----------	-------------

15W			25.4*25.4*11.7mm(1*1*0.46inch)				C			
Pin Assignment										
PIN NO.	1	2	3	4	5	6				
Single O/P	+Vin	GND	+Vo	TRIM	0V	REM				
*Note: The power modules such as the definition of the pin does not match with the hand book,please refer to the actual item.										