


Typical Performance

FEATURES

- Wide input voltage range
- Typical efficiency :82%
- Switching frequency: 100KHz
- Overcurrent/Short circuit protection,Self-furbish
- Input-output isolate
- PCB board in-line type installs
- metal case



3-Years Product Warranty

Technology parameter Test condition:General Nominal Line,Tc=25°C , Rated resistant load unless other wisespecified

Input Feature	Min	Nom	Max	Notes
Input voltage (Vac)	165(200Vdc)	220	265(380Vdc)	N
	85(120Vdc)	220	265(380Vdc)	W
Frequency range (Hz)	47		440	
Remote ON/OFF				NONE

Output Feature

Voltage accuracy		Vo1; Vo2	±1.0%, ±3.0%
Line regulation	Nominal load,full voltage input range	Vo1; Vo2	±0.1%; ±1.5%
Load regulation	Nominal input voltage,20% ~ 100% Nominal load	Vo1; Vo2	±0.5%; ±3.0%
Ripple and noise	20MHz BM,test by 20M oscillograph		≤1%Vo
Peak deviation	25% Rated Load Vary	ΔVo1/ Vo1	≤±5.0%
Dynamic response setting time			≤200us

General Feature

Efficiency			82% typical
Switching frequency			100KHz
Operating temperature			-20°C ~ +55°C
Storage temperature			-40°C ~ +105°C
Max case temperature			+90°C

Relative humidity			10%~90%
case material			Metal case
Isolation voltage		Input-Output	2500Vac/1min
		Input-Case	2500Vac/1min
		Output-Case	500Vac/1min
Temperature coefficient			≤±0.03%/°C
Cooling			Natural convection
MTBF	BELLCORE TR332, (25°C)		2X10 ⁵ Hrs

NOTE:

(1)The 3-15W module working environment temperature more than 55 °C need derating use (- 0.6W/°C for 30W, - 0.86W/°C for 50W), but the max shell temperature shall not be more than 90 °C.

(2)Capacitive load:

The output of the module can be applied electrolytic capacitor, but too much capacity and low ESR may cause the module instability, or cause current limiting point become low,we recommend 100 uF/A of the output capacitance , the current is rated output current.

Product Nomination Method

example	L A 25 - 220 S 05 J		
	① ② ③	④ ⑤ ⑥ ⑦	
①	Wide input voltage range: AC85-265V Narrow input voltage range: AC165-265V	⑤	S=Single route output, D=Dual route output, T=Triple route output, Q=Quadruple output
②	Power adaptation mode: A (AC-DC)	⑥	output voltage
③	Output power(W)	⑦	I: Dual output isolated
④	Normal input voltage		J: Military level

Product Program


PART #	Input voltage range	Output voltage / current					
		VO1		VO2		VO3	
		V	mA	V	mA	V	mA
LA30-220S05A	220V(85~265VAC) 120~380VDC	5V	6000mA				
LA30-220S09A		9V	3333mA				
LA30-220S12A		12V	2500mA				
LA30-220S24A		24V	1250mA				
LA30-220D05A		+5V	3000mA	-5V	3000mA		
LA30-220D12A		+12V	1250mA	-12V	1250mA		

LA30-220D24A		+24V	625mA	-24V	625mA		
--------------	--	------	-------	------	-------	--	--

*NOTE:

The output ripple noise (peak value) measurement, please reference module test instructions.


Mechanical Dimension



BOTTOM VIEW

UNIT:mm(inch)

Temperature Curve



Mechanical Data

WATT	L x W x H	Packing No.
------	-----------	-------------

30W		76.2×76.2×18.0mm(3*3*0.7inch)						A	
Pin Assignment									
PIN	1	2	3	4	5	6	7	8	
Single O/P	FG	Vin	Vin	-S	TRIM	+S	GND	Vout	
Dual O/P	FG	Vin	Vin	Vout2	NP	GND	NP	Vout1	
Dual Isolation O/P	FG	Vin	Vin	-Vout1	+Vout1	NP	-Vout2	+out2	
Note: The power modules such as the definition of the pin does not match with the hand book,please refer to the actual item.									