

Typical Performance

FEATURES

- Wide Input voltage range (2:1、 4:1)
- Typical Efficiency:91%
- Switching frequency: 300KHz ± 30 KHz
- Overcurrent,under voltage protect,short circuit protection,Self-furbish
- Input-output isolate 1500VDC
- PCB Board in-line type installs



3-Years Product Warranty

Technology parameter Test condition:General Nominal Line,Tc=25°C , Rated resistant load unless other wispecified

Input Feature	Min	Nom	Max	Notes
Input voltage(Vdc)	9	12	18	W 2:1
	18	24	36	W 2:1
	36	48	72	W 2:1
	72	110	144	W 2:1
	9	18	36	W 4:1
	18	36	72	W 4:1
Turn on voltage	3.5Vdc		+Vin	Converter guaranteed on when REM pin is left open
Turn off voltage	0		0.3Vdc	

Under voltage protect

Output Feature

Voltage accuracy		Vo1	±1.0%
Line regulation		Vo1	±0.2%
Load regulation	20% ~ 100%	Vo1	±0.5%
Ripple and noise	20MHz BM Vo≤5.0V, ≤50mVp-p; Vo≥48V, ≤180mVp-p; Other, ≤100mVp-p;		
Dynamic response	25%	ΔVo1/Δt	±4.0/500us%
Voltage adjust	Standard output voltage	TRIM	±10%(adjustable)
Start delay time	typical		≤200mS

General Feature

Efficiency	Normal input , full load	Vo≤5.0V,80% typical	Vo>5.0V, 87% typical
Switching frequency		300KHz typical	Max 330KHz
Operating temperature	Free air	Industrial level	-25℃ ~ +55℃
Storage temperature			-40℃ ~ +105℃
Max case temperature			+95℃
Relative humidity			10%~90%
case material			Metal case
Isolation Voltage	500Vdc ≤0.5mA/1min,500Vdc ≤0.5mA/1min		
MTBF	2X10 ⁵ Hrs		

Product Nomination Method


example	L D 25 - 48 S 05 I ① ② ③ ④ ⑤ ⑥ ⑦						
①	Wide input voltage: 2: 1			⑥	output voltage		
②	Power adaptation mode: D (DC-DC)			⑦	I: Dual Route output Isolate		
③	Output power(W)				W: Super Wide input voltage		
④	Normal input voltage						
⑤	S=Single route output, D=Dual route output, T=Triple route output, Q=Quadruple output						

Product Program

PART #	Input voltage range	Output voltage / current					
		VO1		VO2		VO3	
		V	mA	V	mA	V	mA
LD15-12S05C	12V(9~18V)	5V	3000mA				
LD15-12S12C		12V	1250mA				
LD15-12S15C		15V	1000mA				
LD15-18S05C	18V(9~36V)	5V	3000mA				
LD15-18S12C		12V	1250mA				
LD15-18S15C		15V	1000mA				
LD15-24S05C	24V(18~36V)	5V	3000mA				
LD15-24S12C		12V	1250mA				
LD15-24S15C		15V	1000mA				
LD15-36S05C	36V(18~72V)	5V	3000mA				

LD15-36S12C		12V	1250mA				
LD15-36S15C		15V	1000mA				
LD15-48S05C	48V(36~72V)	5V	3000mA				
LD15-48S12C		12V	1250mA				
LD15-48S15C		15V	1000mA				
LD15-110S05C	110V(72~144V)	5V	3000mA				
LD15-110S12C		12V	1250mA				
LD15-110S15C		15V	1000mA				


Mechanical Dimension



BOTTOM VIEW

UNIT:mm(inch)

Temperature Curve



Mechanical Data

WATT	L x W x H	Packing No.
15W	25.4*25.4*11.7mm(1*1*0.46inch)	C

Pin Assignment

PIN NO.	1	2	3	4	5	6				
Single O/P	+Vin	GND	+Vo	TRIM	0V	REM				

*Note: The power modules such as the definition of the pin does not match with the hand book, please refer to the actual item.